

**Order Code:** WP15NW

30W - 1500mm Weatherproof - IP65 - 4000K

### Features

- Ideal for replacement of linear fluorescent fixtures
- Up to 120 lumens per watt efficacy

### Construction

- Polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- Supplied as standard with neutral white [4000K] LED



Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.



### Technical Data

| General               |      | Electrical                |                  |
|-----------------------|------|---------------------------|------------------|
| Luminaire Wattage (W) | 30   | Power Factor (pf)         | 0.9              |
| Weight (kg)           | 2.24 | Input Voltage Range (VAC) | 230              |
| Light Output          |      | Inrush Current Peak (A)   | 1                |
|                       |      | Surge Protection (kV)     | 2                |
|                       |      | Conductor Size (mm)       | 2.5              |
| Lumens (lm)           | 3600 | Terminal Type             | 3 pole piano key |
| Efficacy (lm/W)       | 120  |                           |                  |
| LED                   |      |                           |                  |
| CCT (K)               | 4000 |                           |                  |
| Driver                |      |                           |                  |
| Driver Current (mA)   | 125  |                           |                  |

**Order Code: WP15NW**

30W - 1500mm Weatherproof - IP65 - 4000K

Dimensions

|        |      |
|--------|------|
| A (mm) | 1575 |
| B (mm) | 67   |
| C (mm) | 73   |

Line Drawing

