

Order Code: WP15NWM3

30W - 1500mm Weatherproof - IP65 - 3hrs Maintained Emergency - 4000K

Features

- Ideal for replacement of linear fluorescent fixtures
- Up to 120 lumens per watt efficacy

Construction

- Polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- Supplied as standard with neutral white [4000K] LED



Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.



Technical Data

General		Electrical	
Luminaire Wattage (W)	30	Power Factor (pf)	0.9
Weight (kg)	2.38	Inrush Current Peak (A)	1
Light Output		Surge Protection (kV)	2
		Lumens (lm)	3600
		Conductor Size (mm)	2.5
Efficacy (lm/W)	120	Terminal Type	4 pole piano key
LED			
CCT (K)	4000		
Driver			
Driver Current (mA)	125		

Order Code: WP15NWM3

30W - 1500mm Weatherproof - IP65 - 3hrs Maintained Emergency - 4000K

Dimensions

A (mm)	1565
B (mm)	100
C (mm)	106

Line Drawing

