

**Order Code: WP15NWM3**

30W - 1500mm Weatherproof - IP65 - 3hrs Maintained Emergency - 4000K

**Features**

- Ideal for replacement of linear fluorescent fixtures
- Up to 120 lumens per watt efficacy

**Construction**

- Polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- Supplied as standard with neutral white [4000K] LED



Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	30	Power Factor (pf)	0.9
Weight (kg)	2.38	Inrush Current Peak (A)	1
Light Output		Surge Protection (kV)	2
		Conductor Size (mm)	2.5
		Terminal Type	4 pole piano key
Lumens (lm)	3600		
Efficacy (lm/W)	120		
LED			
CCT (K)	4000		
Driver			
Driver Current (mA)	125		

**Order Code:** WP15NWM3

30W - 1500mm Weatherproof - IP65 - 3hrs Maintained Emergency - 4000K

### Dimensions

A (mm)	1565
B (mm)	100
C (mm)	106

### Line Drawing

