

### Order Code: WP25NW

62W - 1500mm Twin Body Weatherproof - IP65 - 4000K

#### Features

- Ideal for replacement of linear fluorescent fixtures
- Up to 118 lumens per watt efficacy

#### Construction

- Polycarbonate body
- Supplied with opal diffuser
- Integral emergency option available
- Stainless steel fixing clips
- Supplied as standard with neutral white [4000K] LED



Note: This luminaire is not suitable for all chemical environments, please contact us for advice if this luminaire may be exposed to, oil, grease, solvents, acids, alkaline or any similar chemicals.



#### Technical Data

General		Electrical	
Luminaire Wattage (W)	62	Power Factor (pf)	0.9
Weight (kg)	3.31	Input Voltage Range (VAC)	230
Light Output		Inrush Current Peak (A)	1
		Surge Protection (kV)	2
		Conductor Size (mm)	2.5
Lumens (lm)	7300	Terminal Type	3 pole piano key
Efficacy (lm/W)	118		
LED			
CCT (K)	4000		
Driver			
Driver Current (mA)	125		

**Order Code:** WP25NW

62W - 1500mm Twin Body Weatherproof - IP65 - 4000K

### Dimensions

A (mm)	1575
B (mm)	105
C (mm)	73

### Line Drawing

