

Order Code: XCBD11NWM3PC

11W - Decorative Weatherproof IP65 Bulkhead with Opal Diffuser - Photocell - 3hrs Maintained Emergency - 4000K



Features

- Ideal for retrofit of existing 2D fixtures
- Suitable for exterior use, outdoor or walkways
- Choice of plain or eyelid optic
- Up to 109 lumens per watt efficacy

Construction

- Polycarbonate body
- Opal diffuser
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED



Technical Data

General		Electrical	
Luminaire Wattage (W)	11	Rated Input Current (A)	0.14
Weight (kg)	0.76	Power Factor (pf)	0.9
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	220-240
Light Output		Inrush Current Peak (A)	24.4
Lumens (lm)	1200	Surge Protection (kV)	0.5
Efficacy (lm/W)	109	Conductor Size (mm)	2.5
LED		Terminal Type	4 pole piano key
CCT (K)	4000		
CRI	80		
Macadam Elipses	4		
Emergency			
Emergency Lumen Operating	218		
Emergency Wattage (W)	3		

Order Code: XCBD11NWM3PC

11W - Decorative Weatherproof IP65 Bulkhead with Opal Diffuser - Photocell - 3hrs Maintained Emergency - 4000K

Dimensions

C (mm)	60

Dia. (mm)	275

Line Drawing

