


Order Code: XCBH12CTM3HFSGT

XCITE RETRO FIT GEAR TRAY XCBH 14W - Fixed output - Emergency - Microwave sensor - 3000K-6500K



Features

- CCT selectable via selector switch [3000K/4000K/6500K]
- Microwave movement sensor available
- Up to 148 lumens per watt efficacy

Construction

- Emergency option available

Installation Notes

Universal fitting suitable for various circular enclosures



Technical Data

General		Electrical	
Luminaire Wattage (W)	14.2	Rated Input Current (A)	0.09
Weight (kg)	0.43	Power Factor (pf)	0.72
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	198 - 264
		Inrush Current Peak (A)	292
		Surge Protection (kV)	1 kV
		Conductor Size (mm)	0.5 to 2.5
		Terminal Type	SLK series 4 to pole grip to wire
Light Output			
Lumens (lm)	2100		
Efficacy (lm/W)	148		
LED			
CCT (K)	3000K/4000K/6500K		
CRI	80		
Macadam Ellipses	3		
Driver			
Driver Current (mA)	350		
Forward Voltage (V)	32.6		
Emergency			
Emergency Lumen Operating	155		
Emergency Wattage (W)	1		

Order Code: XCBH12CTM3HFSGT

XCITE RETRO FIT GEAR TRAY XCBH 14W - Fixed output - Emergency - Microwave sensor - 3000K-6500K

Dimensions

C (mm)	40
Dia. (mm)	265

Line Drawing

