

Order Code: XCBH12CTM3HFSPC

12W - Circular Bulkhead - IP65 - Microwave Sensor - 3hrs Maintained Emergency - CCTK Selector [3000K/4000K/6000K] - Polished Chrome



Features

- Ideal for retrofit of existing 2D fixtures
- Suitable for bathrooms or storerooms
- Microwave movement sensor available
- CCT selectable via selector switch [3000K/4000K/6000K]
- Up to 92 lumens per watt efficacy

Construction

- Polished Chrome finish available
- Polycarbonate body
- Integral emergency option available



Technical Data

| General | | Electrical | |
|-------------------------------|-------------------|---------------------------|-------------------|
| Luminaire Wattage (W) | 12 | Rated Input Current (A) | 0.07 |
| Weight (kg) | 1.20 | Power Factor (pf) | 0.7 |
| Operating Temperature (ta °C) | 5 to 25 | Input Voltage Range (VAC) | 220-240 |
| | | Inrush Current Peak (A) | 10 |
| | | Surge Protection (kV) | 1 |
| | | Conductor Size (mm) | 2.5 |
| | | Terminal Type | 4 pole screw down |
| Light Output | | | |
| Lumens (lm) | 1000 to 1100 | | |
| Efficacy (lm/W) | 92 | | |
| LED | | | |
| CCT (K) | 3000K/4000K/6000K | | |
| CRI | 80 | | |
| Macadam Ellipses | 4 | | |
| Emergency | | | |
| Emergency Lumen Operating | 140 | | |
| Emergency Wattage (W) | 2 | | |

Order Code: XCBH12CTM3HFSPC

12W - Circular Bulkhead - IP65 - Microwave Sensor - 3hrs Maintained Emergency - CCTK Selector [3000K/4000K/6000K] - Polished Chrome

Dimensions

| | |
|-----------|-----|
| C (mm) | 110 |
| Dia. (mm) | 330 |

Line Drawing

