

### Order Code: XCBH12CTM3HFSPC

12W - Circular Bulkhead - IP65 - Microwave Sensor - 3hrs Maintained Emergency - CCTK Selector [3000K/4000K/6000K] - Polished Chrome



#### Features

- Ideal for retrofit of existing 2D fixtures
- Suitable for bathrooms or storerooms
- Microwave movement sensor available
- CCT selectable via selector switch [3000K/4000K/6000K]
- Up to 92 lumens per watt efficacy

#### Construction

- Polycarbonate body
- Polished Chrome finish available
- Integral emergency option available



#### Technical Data

General		Electrical	
Luminaire Wattage (W)	12	Rated Input Current (A)	0.07
Weight (kg)	1.20	Power Factor (pf)	0.7
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	220-240
Light Output		Inrush Current Peak (A)	10
		Surge Protection (kV)	1
		Conductor Size (mm)	2.5
Lumens (lm)	1000 to 1100	Terminal Type	4 pole screw down
Efficacy (lm/W)	92		
LED			
CCT (K)	3000K/4000K/6000K		
CRI	80		
Macadam Ellipses	4		
Emergency			
Emergency Lumen Operating	140		
Emergency Wattage (W)	2		

### Order Code: XCBH12CTM3HFSPC

12W - Circular Bulkhead - IP65 - Microwave Sensor - 3hrs Maintained Emergency - CCTK Selector [3000K/4000K/6000K] - Polished Chrome

#### Dimensions

C (mm)	110
Dia. (mm)	330

#### Line Drawing

