

Order Code: XCBH12CTM3PC

12W - Circular Bulkhead - IP65 - 3hr Maintained Emergency - CCTK Selector [3000K/4000K/6000K] - Polished Chrome



Features

- Ideal for retrofit of existing 2D fixtures
- Suitable for bathrooms or storerooms
- Microwave movement sensor available
- CCT adjustable via selector switch [3000K/4000K/6000K]
- Up to 92 lumens per watt efficacy

Construction

- Polycarbonate body
- Polished Chrome finish available
- Integral emergency option available



Technical Data

General

| | |
|-------------------------------|---------|
| Luminaire Wattage (W) | 12 |
| Weight (kg) | 1.15 |
| Operating Temperature (ta °C) | 5 to 25 |

Light Output

| | |
|-----------------|--------------|
| Lumens (lm) | 1000 to 1100 |
| Efficacy (lm/W) | 92 |

LED

| | |
|-----------------|-------------------|
| CCT (K) | 3000K/4000K/6000K |
| CRI | 80 |
| Macadam Elipses | 4 |

Emergency

| | |
|---------------------------|-----|
| Emergency Lumen Operating | 140 |
| Emergency Wattage (W) | 2 |

Electrical

| | |
|---------------------------|-------------------|
| Rated Input Current (A) | 0.07 |
| Power Factor (pf) | 0.7 |
| Input Voltage Range (VAC) | 220-240 |
| Inrush Current Peak (A) | 10 |
| Surge Protection (kV) | 1 |
| Conductor Size (mm) | 2.5 |
| Terminal Type | 4 pole screw down |

Order Code: XCBH12CTM3PC

12W - Circular Bulkhead - IP65 - 3hr Maintained Emergency - CCTK Selector [3000K/4000K/6000K] - Polished Chrome

Dimensions

| | |
|-----------|-----|
| C (mm) | 110 |
| Dia. (mm) | 330 |

Line Drawing

