

**Order Code: XCBHC6**

6W - Bulkhead Wall Light with Opal Polycarbonate Diffuser - IP65 - 6000K - Black



**Features**

- Suitable for exterior walls and entrance areas
- Photocell option available
- Up to 67 lumens per watt efficacy

**Construction**

- Black polycarbonate body
- High quality polycarbonate construction
- Shallow profile diffuser
- Opal polycarbonate diffuser
- Supplied with daylight [6000K]



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	6	Rated Input Current (A)	0.05
Weight (kg)	0.38	Power Factor (pf)	0.5
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
<b>Light Output</b>		Inrush Current Peak (A)	25
Lumens (lm)	400	Surge Protection (kV)	1
Efficacy (lm/W)	67	Conductor Size (mm)	2.5
<b>LED</b>		Terminal Type	3 pole piano key
CCT (K)	6000		
CRI	80		
Macadam Ellipses	4		

**Order Code: XCBHC6**

6W - Bulkhead Wall Light with Opal Polycarbonate Diffuser - IP65 - 6000K - Black

Dimensions

A (mm)	245
B (mm)	125
C (mm)	97

Line Drawing

