

Order Code: XCBHC6

6W - Bulkhead Wall Light with Opal Polycarbonate Diffuser - IP65 - 6000K - Black



Features

- Suitable for exterior walls and entrance areas
- Photocell option available
- Up to 67 lumens per watt efficacy

Construction

- Black polycarbonate body
- High quality polycarbonate construction
- Opal polycarbonate diffuser
- Shallow profile diffuser
- Supplied with daylight [6000K]



Technical Data

| General | | Electrical | |
|-------------------------------|---------|---------------------------|------------------|
| Luminaire Wattage (W) | 6 | Rated Input Current (A) | 0.05 |
| Weight (kg) | 0.38 | Power Factor (pf) | 0.5 |
| Operating Temperature (ta °C) | 0 to 25 | Input Voltage Range (VAC) | 220-240 |
| Light Output | | Inrush Current Peak (A) | 25 |
| Lumens (lm) | 400 | Surge Protection (kV) | 1 |
| Efficacy (lm/W) | 67 | Conductor Size (mm) | 2.5 |
| LED | | Terminal Type | 3 pole piano key |
| CCT (K) | 6000 | | |
| CRI | 80 | | |
| Macadam Elipses | 4 | | |

Order Code: XCBHC6

6W - Bulkhead Wall Light with Opal Polycarbonate Diffuser - IP65 - 6000K - Black

Dimensions

| | |
|--------|-----|
| A (mm) | 245 |
| B (mm) | 125 |
| C (mm) | 97 |

Line Drawing

