

Order Code: XCBHCBOX1

X1 Bulkhead WP - Circular - Opal diffuser - CCT [3000K/4000K/6000K] + Wattage Selectable - Black



Features

- Suitable for exterior commercial and industrial applications
- CCT selectable via selector switch [3000K/4000K/6000K]
- Wattage selectable via selector switch [8W/12W/16W]

Construction

- Modular [emergency](#) and [microwave sensor](#)'s available for quick and easy conversion of a standard fitting
- For additional control, please use [X1 Bulkhead Remote](#) [Sold Separately]

Installation Notes

3-point screw fixing
 Conduit side entry points for surface mount cable entry
 Loop-in, loop-out push-fit terminal block for quick tool-free instalation



Technical Data

General

| | |
|-------------------------------|------------|
| Luminaire Wattage (W) | 8W/12W/16W |
| Weight (kg) | 0.69 |
| Operating Temperature (ta °C) | 0° to 25° |

Light Output

| | |
|-----------------|--------------|
| Lumens (lm) | 1070 to 1930 |
| Efficacy (lm/W) | 128 |

LED

| | |
|-----------------|-------------------|
| CCT (K) | 3000K/4000K/6000K |
| CRI | 80 |
| Macadam Elipses | 1 to 1.5 |

Driver

| | |
|---------------------|--------------|
| Driver Current (mA) | 140/215/280 |
| Forward Voltage (V) | 48.5 to 52.5 |

Electrical

| | |
|---------------------------|------------------|
| Rated Input Current (A) | 0.04 to 0.08 |
| Power Factor (pf) | 0.83 to 0.92 |
| Input Voltage Range (VAC) | 198 to 264 |
| Inrush Current Peak (A) | 19.1 |
| Surge Protection (kV) | 1 |
| Conductor Size (mm) | 0.5 to 2.5 |
| Terminal Type | 4 pole piano key |

Order Code: XCBHCBOX1

X1 Bulkhead WP - Circular - Opal diffuser - CCT [3000K/4000K/6000K] + Wattage Selectable - Black

Dimensions

| | |
|-----------|-----|
| C (mm) | 85 |
| ----- | |
| Dia. (mm) | 282 |
| ----- | |

Line Drawing

