

Order Code: XCBHLX1WM3MS

X1 Bulkhead Large - White - CCT [3000K/4000K/6000K] + Wattage Selectable [12/16/20W] - Fixed output - Opal diffuser - Fixed output - Microwave sensor



Features

- 12W, 16W and 20W wattage selectable
Allows the output to be matched to the lighting requirements of the space
- 3000K, 4000K and 6000K selectable
Enables the lighting colour to be tailored to suit different environments and user preferences
- 1800 lm to 3000 lm output range
Provides suitable light levels for a wide range of communal spaces
- Large diameter design
Provides increased coverage and a more prominent appearance within the space

Construction

- Microwave sensor option available
Supports additional energy savings through automatic occupancy based lighting control
- Emergency option available
Maintains illumination during mains power failure to support safe evacuation of the building
- Aluminium body
Provides a durable, corrosion resistant housing with excellent longevity
- Polycarbonate opal diffuser
Provides enhanced impact resistance, helping the luminaire achieve an IK06 rating for improved durability

Technical Data

General

Table with 2 columns: General, 12W/16W/20W. Rows: Luminaire Wattage (W), Weight (kg), Operating Temperature (ta °C).

Light Output

Table with 2 columns: Light Output, 1800/2500/3000. Rows: Lumens (lm), Efficacy (lm/W).

LED

Table with 2 columns: LED, 3000K/4000K/6000K. Rows: CCT (K), CRI, Macadam Elipses.

Driver

Table with 2 columns: Driver, 90, 120, 155. Rows: Driver Current (mA), Forward Voltage (V).

Emergency

Table with 2 columns: Emergency, 97. Rows: Emergency Lumen Operating, Emergency Wattage (W).

Electrical

Table with 2 columns: Electrical, 0.05 to 0.09. Rows: Rated Input Current (A), Power Factor (pf), Input Voltage Range (VAC), Inrush Current Peak (A), Surge Protection (kV), Conductor Size (mm), Terminal Type.

Order Code: XCBHLX1WM3MS

X1 Bulkhead Large - White - CCT [3000K/4000K/6000K] + Wattage Selectable [12/16/20W] - Fixed output - Opal diffuser - Fixed output - Microwave sensor

Dimensions

C (mm)	102
Dia. (mm)	435

Line Drawing

