

**Order Code: XCBHWPCBOM3HFS**

16W - Circular Bulkhead with Opal Diffuser - IP65 - 3hrs Maintained Emergency - 4000K - Black Base - Microwave Sensor



**Features**

- Suitable for general interior or exterior use
- 20mm conduit side cable entries for wall or ceiling fix
- Up to 94 lumens per watt efficacy

**Construction**

- High quality polycarbonate construction
- Polycarbonate body
- White base or black base available
- Opal or prismatic diffuser available
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	16	Rated Input Current (A)	0.07
Weight (kg)	1.18	Power Factor (pf)	0.85
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	220-240
<b>Light Output</b>		Inrush Current Peak (A)	10
Lumens (lm)	1500	Surge Protection (kV)	1
Efficacy (lm/W)	94	Conductor Size (mm)	2.5
<b>LED</b>		Terminal Type	4 pole screw down
CCT (K)	4000		
CRI	80		
Macadam Elipses	4		
<b>Emergency</b>			
Emergency Lumen Operating	210		
Emergency Wattage (W)	2		

### Order Code: XCBHWPCBOM3HFS

16W - Circular Bulkhead with Opal Diffuser - IP65 - 3hrs Maintained Emergency - 4000K - Black Base - Microwave Sensor

#### Dimensions

C (mm)	85
Dia. (mm)	282

#### Line Drawing

