

Order Code: XCBHX1M3MS

X1 Bulkhead - CCT [3000K/4000K/6000K] + Wattage Selectable - Emergency - Microwave sensor



Features

- Suitable for most domestic and commercial applications
- CCT selectable via selector switch [3000K/4000K/6000K]
- Wattage selectable via selector switch [8W/12W/16W]
- Twist On/Off diffuser with screwlock suitable for public spaces
- Hinged gear tray for quick and easy installation

Construction

- Manufactured from durable thermoplastic materials
- Modular [emergency](#) and [microwave sensor](#)'s available for quick and easy conversion of a standard fitting
- For additional control, please use [X1 Bulkhead Remote](#) [Sold Separately]
- Pre-assembled emergency and sensor luminaires available

Installation Notes

Conduit side entry points for surface mount cable entry
Loop in/out push-fit terminal block for quick installation

Technical Data

General

| | |
|-------------------------------|------------|
| Luminaire Wattage (W) | 8W/12W/16W |
| Weight (kg) | 1.47 |
| Operating Temperature (ta °C) | 5° to 25° |

Light Output

| | |
|-----------------|--------------|
| Lumens (lm) | 1000 to 1900 |
| Efficacy (lm/W) | 130 |

LED

| | |
|-----------------|-------------------|
| CCT (K) | 3000K/4000K/6000K |
| CRI | 80 |
| Macadam Elipses | 1.5 to 9.1 |

Driver

| | |
|---------------------|-------------------|
| Driver Current (mA) | 140 to 215 to 280 |
| Forward Voltage (V) | 47.6 to 50 |

Emergency

| | |
|---------------------------|-----|
| Emergency Lumen Operating | 135 |
| Emergency Wattage (W) | 2 |

Electrical

| | |
|---------------------------|------------------|
| Rated Input Current (A) | 0.04 to 0.07 |
| Power Factor (pf) | 0.82 to 0.92 |
| Input Voltage Range (VAC) | 220 to 240 |
| Inrush Current Peak (A) | 18.9 |
| Surge Protection (kV) | 1KV |
| Conductor Size (mm) | 0.5 to 2.5 |
| Terminal Type | 4 pole piano key |

Order Code: XCBHX1M3MS

X1 Bulkhead - CCT [3000K/4000K/6000K] + Wattage Selectable - Emergency - Microwave sensor

Dimensions

| | |
|-----------|-----|
| C (mm) | 85 |
| ----- | |
| Dia. (mm) | 320 |
| ----- | |

Line Drawing

