

Order Code: XCBLC12CTD

12W - Downlight BL CC - CCTK Selector [3000K/4000K/6000K]- Dimmable



Features

- Suitable for general domestic and commercial use
- CCT adjustable via selector switch [3000K/4000K/6000K]
- Available in 6 sizes
- Available in 6 different outputs
- Phase cut dimming option available
- 3 hours emergency maintained with compatible conversion box [Emergency Kit](#)
- Up to 100 lumens per watt efficacy

Construction

- Frosted polycarbonate diffuser



Technical Data

General		Electrical	
Luminaire Wattage (W)	12	Rated Input Current (A)	0.06
Weight (kg)	0.19	Power Factor (pf)	0.92
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	198-264
		Inrush Current Peak (A)	2.14
		Surge Protection (kV)	1
		Conductor Size (mm)	0.75 - 1.5 mm ²
		Terminal Type	PUSH BUTTON 2
Light Output			
Lumens (lm)	1200		
Efficacy (lm/W)	100		
LED			
CCT (K)	3000K/4000K/6000K		
CRI	80		
Macadam Ellipses	4		
Driver			
Driver Current (mA)	300		
Forward Voltage (V)	32-48		

Order Code: XCBLC12CTD

12W - Downlight BL CC - CCTK Selector [3000K/4000K/6000K]- Dimmable

Dimensions

C (mm)	26
Cut Out (mm)	150
Dia. (mm)	170

Line Drawing

