

Order Code: XCBOLX1LGC

X1 Bollard XCBOL - Grey - [3000K/4000K/5000K] + Wattage Switchable - Cone - Fixed output



Features

- CCT adjustable via selector switch [3000K/4000K/5000K]
- Wattage adjustable via 2-way dip switch [12W/16W/20W]
- Up to 103 lumens per watt efficacy
- Ground Mounting [J-BOLT KIT](#) [sold separately]

Construction

- Weatherproof IP65 construction
- Loop in/out mains connector
- Die-cast aluminium construction designed to resist corrosion and prevent rust, finished in black [RAL 9005]

Technical Data

General

| | |
|-------------------------------|-------------|
| Luminaire Wattage (W) | 12W/16W/20W |
| Weight (kg) | 3.29 |
| Operating Temperature (ta °C) | -20 to +50 |

Light Output

| | |
|-----------------|--------------|
| Lumens (lm) | 1100 to 1800 |
| Efficacy (lm/W) | 103 |

LED

| | |
|-----------------|-------------------|
| CCT (K) | 3000K/4000K/5000K |
| CRI | 80 |
| Macadam Elipses | 5.4 |

Driver

| | |
|---------------------|----------|
| Driver Current (mA) | 285 |
| Forward Voltage (V) | 50 to 70 |

Electrical

| | |
|---------------------------|--------------|
| Rated Input Current (A) | 0.05 to 0.09 |
| Power Factor (pf) | 0.9 to 0.96 |
| Input Voltage Range (VAC) | 220 to 240 |
| Inrush Current Peak (A) | 11.13 |
| Surge Protection (kV) | 4 |
| Terminal Type | 3 Pole |

Order Code: XCBOLX1LGC

X1 Bollard XCBOL - Grey - [3000K/4000K/5000K] + Wattage Switchable - Cone - Fixed output

Dimensions

| | |
|-----------|------|
| C (mm) | 1000 |
| ----- | |
| Dia. (mm) | 120 |
| ----- | |

Line Drawing

