

**Order Code: XCCDL3NWSN**

3W - Circular Under Cabinet Downlight - IP20 - 4000K - Satin Nickel



**Features**

- LED circular under cabinet downlight
- Suitable for kitchen or wardrobe applications
- Can be surface or flush/recessed mounted
- Complete with 0.5m of mains, 2 core cable
- Up to 67 lumens per watt efficacy

**Construction**

- Pressed steel body
- Frosted polycarbonate diffuser
- Integral driver circuitry with mains input
- Available in warm white [3000K] or neutral white [4000K]

Note: Please note dimensions relate to the 'surface' fitting [WITH TRIM]. The dimensions [WITHOUT TRIM] for recessed install are [Cut-out. 60mm] [Dia. 68mm] [C. 23mm]



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	3	Rated Input Current (A)	0.011
Weight (kg)	0.17	Power Factor (pf)	0.4
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
Light Output		Surge Protection (kV)	2
		Conductor Size (mm)	0.5
		Terminal Type	Bare wire
Lumens (lm)	200		
Efficacy (lm/W)	67		
LED			
CCT (K)	4000		
CRI	80		
Macadam Ellipses	3		

**Order Code:** XCCDL3NWSN

3W - Circular Under Cabinet Downlight - IP20 - 4000K - Satin Nickel

Dimensions

C (mm)	23
Cut Out (mm)	68
Dia. (mm)	74

Line Drawing

