

Order Code: XCDL4DL

4W - Downlight Ultra Slim Low Profile - IP20 - 6000K



Features

- Ideal for retrofit of existing CFL Fixtures
- Suitable for general circulation areas
- Available in 6 sizes
- Edge-lit LED array with ultra slim profile
- 3 hours emergency maintained with compatible conversion box [Emergency Kit](#)
- Up to 88 lumens per watt efficacy

Construction

- Die-cast aluminium body
- Opal polystyrene diffuser - TP[b]
- Plug and play driver
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]



Technical Data

| General | | Electrical | |
|-------------------------------|---------|---------------------------|------------------|
| Luminaire Wattage (W) | 4 | Rated Input Current (A) | 0.02 |
| Weight (kg) | 0.15 | Power Factor (pf) | 0.9 |
| Operating Temperature (ta °C) | 0 to 25 | Input Voltage Range (VAC) | 200-240 |
| Light Output | | Inrush Current Peak (A) | 6.84 |
| Lumens (lm) | 350 | Surge Protection (kV) | 2 |
| Efficacy (lm/W) | 88 | Conductor Size (mm) | 1.5 |
| LED | | Terminal Type | 2 pole grip wire |
| CCT (K) | 6000 | | |
| CRI | 80 | | |
| Macadam Elipses | 4 | | |
| Driver | | | |
| Driver Current (mA) | 130 | | |
| Forward Voltage (V) | 28-31 | | |

Order Code: XCDL4DL

4W - Downlight Ultra Slim Low Profile - IP20 - 6000K

Dimensions

| | |
|--------------|----|
| C (mm) | 25 |
| Cut Out (mm) | 72 |
| Dia. (mm) | 90 |

Line Drawing

