

### Order Code: XCDL8WW

8W - Downlight Ultra Slim Low Profile - IP20 - 3000K



#### Features

- Ideal for retrofit of existing CFL Fixtures
- Suitable for general circulation areas
- Available in 6 sizes
- Edge-lit LED array with ultra slim profile
- 3 hours emergency maintained with compatible conversion box [Emergency Kit](#)
- Up to 75 lumens per watt efficacy

#### Construction

- Die-cast aluminium body
- Opal polystyrene diffuser - TP[b]
- Plug and play driver
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]



#### Technical Data

General		Electrical	
Luminaire Wattage (W)	8	Rated Input Current (A)	0.04
Weight (kg)	0.19	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	200-240
Light Output		Inrush Current Peak (A)	6.84
		Surge Protection (kV)	2
Lumens (lm)	600	Conductor Size (mm)	1.5
Efficacy (lm/W)	75	Terminal Type	2 pole grip wire
LED			
CCT (K)	3000		
CRI	80		
Macadam Elipses	4		
Driver			
Driver Current (mA)	180		
Forward Voltage (V)	28-31		

**Order Code:** XCDL8WW

8W - Downlight Ultra Slim Low Profile - IP20 - 3000K

### Dimensions

C (mm)	25
Cut Out (mm)	107
Dia. (mm)	120

### Line Drawing

