

Order Code: XCEMBAM3ST

XCITE EM BULKHEAD ST XCEMBA 3W - 6500K - Fixed output - Emergency Self-test



Features

- Suitable for open areas and escape routes
- 20mm conduit side and rear cable entries for wall or ceiling fix
- Semi recessed bezel available
- Reduced maintenance and high performance
- Supplied with LiFePO4 battery

Construction

- Polycarbonate body and diffuser
- Maintained or non-maintained available
- Supplied with self adhesive universal legend
- Supplied as standard with daylight [6500K] LED
- Integral auto self-test for reduced maintenance, includes a disable function



Technical Data

General		Electrical	
Luminaire Wattage (W)	3	Rated Input Current (A)	0.05
Weight (kg)	0.51	Power Factor (pf)	0.28
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)	220 to 240
Light Output		Conductor Size (mm)	1.5
Efficacy (lm/W)	107	Terminal Type	4 pole piano key
LED			
CRI	70		
Macadam Ellipses	2.1		
Driver			
Driver Current (mA)	360		
Forward Voltage (V)	3.4		
Emergency			
Emergency Lumen Operating	320		
Emergency Wattage (W)	3		

Order Code: XCEMBAM3ST

XCITE EM BULKHEAD ST XCEMBA 3W - 6500K - Fixed output - Emergency Self-test

Dimensions

A (mm)	352
B (mm)	110
C (mm)	65

Line Drawing

