

**Order Code: XCEMBANM3ST**

XCITE EM BULKHEAD ST XCEMBA 1W - 6500K - Fixed output - non-maintained Emergency Self-test



**Features**

- Suitable for open areas and escape routes
- 20mm conduit side and rear cable entries for wall or ceiling fix
- Semi recessed bezel available
- Reduced maintenance and high performance
- Supplied with LiFePO4 battery

**Construction**

- Polycarbonate body and diffuser
- Maintained or non-maintained available
- Supplied with self adhesive universal legend
- Supplied as standard with daylight [6500K] LED
- Integral auto self-test for reduced maintenance, includes a disable function



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	1	Rated Input Current (A)	0.03
Weight (kg)	0.51	Power Factor (pf)	0.17
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)	220 to 240
<b>Light Output</b>		Conductor Size (mm)	1.5
Efficacy (lm/W)	107	Terminal Type	3 pole piano key
<b>LED</b>			
CRI	70		
Macadam Ellipses	2.1		
<b>Driver</b>			
Driver Current (mA)	360		
Forward Voltage (V)	3.4		
<b>Emergency</b>			
Emergency Lumen Operating	107		
Emergency Wattage (W)	1		

**Order Code: XCEMBANM3ST**

XCITE EM BULKHEAD ST XCEMBA 1W - 6500K - Fixed output - non-maintained Emergency Self-test

Dimensions

A (mm)	352
B (mm)	110
C (mm)	65

Line Drawing

