

Order Code: XCFC200NW

200W - High Output Floodlight - 4000K



Features

- Suitable for exterior building and feature lighting
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- High quality toughened safety glass

Construction

- Die-cast aluminium body finished with black marine grade paint finish
- Weatherproof IP65 construction
- Breather gland for reducing condensation
- Supplied as standard with neutral white [4000K] LED



Technical Data

| General | | Electrical | |
|-------------------------------|-----------|---------------------------|-------------|
| Luminaire Wattage (W) | 200 | Rated Input Current (A) | 0.97 |
| Weight (kg) | 2.25 | Power Factor (pf) | 0.9 |
| Operating Temperature (ta °C) | -20 to 25 | Input Voltage Range (VAC) | 220-240 |
| Light Output | | Terminal Type | 3-CORE FLEX |
| Lumens (lm) | 20000 | | |
| Efficacy (lm/W) | 100 | | |
| LED | | | |
| CCT (K) | 4000 | | |
| CRI | >80 | | |
| Macadam Ellipses | 4 | | |
| Driver | | | |
| Driver Current (mA) | 670 | | |
| Forward Voltage (V) | 230 | | |

Order Code: XCFC200NW

200W - High Output Floodlight - 4000K

Dimensions

| | |
|--------|-----|
| A (mm) | 380 |
| B (mm) | 300 |
| C (mm) | 40 |

Line Drawing

