

**Order Code: XCFC20CTP**

20W - Floodlight with PIR - CCTK Selector [3000K/4000K/6000K]



**Features**

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- CCT selectable via selector switch [3000K/4000K/6000K]
- Available with high performance PIR
- Available in 4 different outputs
- Available with microwave sensor + photocell only function (via the remote, supplied as standard)
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Up to 100 lumens per watt efficacy

**Construction**

- Die-cast aluminium body finished with black marine grade paint finish
- Weatherproof IP65 construction
- CRI: Ra>80



**Technical Data**

| General                       |                   | Electrical                |                   |
|-------------------------------|-------------------|---------------------------|-------------------|
| Luminaire Wattage (W)         | 20                | Rated Input Current (A)   | 0.0885            |
| Weight (kg)                   | 0.89              | Power Factor (pf)         | 0.9               |
| Operating Temperature (ta °C) | -20 to 40         | Input Voltage Range (VAC) | 220-240           |
| <b>Light Output</b>           |                   | Terminal Type             | 3 pole screw down |
| Lumens (lm)                   | 2000              |                           |                   |
| Efficacy (lm/W)               | 100               |                           |                   |
| <b>LED</b>                    |                   |                           |                   |
| CCT (K)                       | 3000K/4000K/6000K |                           |                   |
| CRI                           | >80               |                           |                   |
| Macadam Elipses               | <5                |                           |                   |

**Order Code:** XCFC20CTP

20W - Floodlight with PIR - CCTK Selector [3000K/4000K/6000K]

### Dimensions

|        |     |
|--------|-----|
| A (mm) | 208 |
| B (mm) | 207 |
| C (mm) | 52  |

### Line Drawing

