

**Order Code: XCFRA5WWW**

5W - Fire Rated Recessed Mini Downlight - 3000K - White



**Features**

- Compact fire rated downlight with AC on board driver technology
- Dimmable as standard
- Convert to larger sized cut outs with the [Conversion Plates](#)
- 30, 60 & 90 minute fire rating with solid timber joists
- 30 minute fire rating with Staircraft I-Joist and METAL WEB Joist [ [Compatibility Matrix](#) ]
- Up to 80 lumens per watt efficacy

**Construction**

- Loop in/out mains connections with integrated driver
- Steel body providing a high level of fire protection in accordance with Building Regulations Part B
- White, Matt White, Satin Nickel or Polished Chrome Finish
- Available in warm white [3000K] or neutral white [4000K]



**Technical Data**

**General**

Luminaire Wattage (W)	5
Weight (kg)	0.13
Operating Temperature (ta °C)	0 to 25

**Light Output**

Lumens (lm)	400
Efficacy (lm/W)	80

**LED**

CCT (K)	3000
CRI	80
Macadam Elipses	4

**Electrical**

Rated Input Current (A)	0.014
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	5
Conductor Size (mm)	2.5
Terminal Type	3 pole piano key

**Order Code:** XCFRA5WWW

5W - Fire Rated Recessed Mini Downlight - 3000K - White

### Dimensions

C (mm)	80
Cut Out (mm)	60
Dia. (mm)	80

### Line Drawing

