

Order Code: XCHBA200NWMS
200W - High Bay - Microwave sensor - 4000K

Features

- Ideal for retro-fit of SON or Metal Halide high bays
- Available in 2 sizes and 3 outputs
- Suspension via chain or wire suspension
- Suitable for mounting heights between 5m and 12m
- Microwave dimming sensor option available

Construction

- Die-cast aluminium body finished in black
- Integral driver
- Supplied as standard with neutral white [4000K] LED



Technical Data

| General | | Electrical | |
|-------------------------------|-----------|---------------------------|-----------|
| Luminaire Wattage (W) | 200 | Rated Input Current (A) | 0.92 |
| Weight (kg) | 2.59 | Power Factor (pf) | 0.95 |
| Operating Temperature (ta °C) | -20 to 25 | Input Voltage Range (VAC) | 100 - 240 |
| Light Output | | Inrush Current Peak (A) | 350 |
| | | Surge Protection (kV) | 6 |
| | | Conductor Size (mm) | 1 |
| Lumens (lm) | 26000 | Terminal Type | push |
| Efficacy (lm/W) | 130 | | |
| LED | | | |
| CCT (K) | 4000 | | |
| CRI | 80 | | |
| Macadam Ellipses | <3 | | |
| Driver | | | |
| Driver Current (mA) | 750 | | |
| Forward Voltage (V) | 240 | | |

Order Code: XCHBA200NWMS

200W - High Bay - Microwave sensor - 4000K

Dimensions

| | |
|-----------|-----|
| C (mm) | 140 |
| ----- | |
| Dia. (mm) | 361 |
| ----- | |

Line Drawing

