

**Order Code: XCNC5X1M3MS**

1500mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Emergency - Microwave sensor



**Features**

- Suitable for a range of commercial and industrial applications
- Available in 4 lengths [2ft, 4ft, 5ft, and 6ft]
- CCT selectable via selector switch [3000K/4000K/6000K]
- Wattage selectable via 2-way dip switch [29W/36W/43W/50]
- Position adjustable mounting clips
- Stainless steel retainer clips for diffuser with anti-tamper screw

**Construction**

- Grey polycarbonate body
- Weatherproof IP65 construction
- Pre-assembled emergency and sensor luminaires available

**Installation Notes**

Conduit and BESA fixing points for end or rear cable entry  
Loop in/out push-fit terminal block for quick installation

**Technical Data**

**General**

|                               |                |
|-------------------------------|----------------|
| Luminaire Wattage (W)         | 29W/36W/43W/50 |
| Weight (kg)                   | 2.55           |
| Operating Temperature (ta °C) | +5° to +25°    |

**Light Output**

|                 |             |
|-----------------|-------------|
| Lumens (lm)     | 4700 - 7900 |
| Efficacy (lm/W) | 162         |

**LED**

|                 |                   |
|-----------------|-------------------|
| CCT (K)         | 3000K/4000K/6000K |
| CRI             | 80                |
| Macadam Elipses | 6.5               |

**Driver**

|                     |                    |
|---------------------|--------------------|
| Driver Current (mA) | 200, 250, 300, 350 |
| Forward Voltage (V) | 124 to 134.1Vdc    |

**Emergency**

|                           |     |
|---------------------------|-----|
| Emergency Lumen Operating | 327 |
| Emergency Wattage (W)     | 2   |

**Electrical**

|                           |                  |
|---------------------------|------------------|
| Rated Input Current (A)   | 0.14 to 0.24     |
| Power Factor (pf)         | 0.89 to 0.95     |
| Input Voltage Range (VAC) | 220 to 240       |
| Inrush Current Peak (A)   | 45A              |
| Surge Protection (kV)     | 1                |
| Conductor Size (mm)       | 0.5 to 2.5       |
| Terminal Type             | 4 pole piano key |

**Order Code:** XCNC5X1M3MS

1500mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Emergency - Microwave sensor

### Dimensions

|        |      |
|--------|------|
| A (mm) | 1570 |
| B (mm) | 95   |
| B (mm) | 80   |
| Fix    | 600  |

### Line Drawing

