

Order Code: XCPL9WW

9W - Porch Light LED - Fixed Output - 3000K



Features

- Suitable for exterior walls and entrance areas
- Low energy LED module for reduced running costs
- Up to 61 lumens per watt efficacy

Construction

- Die-cast aluminium body finished in Anthracite grey
- Frosted polycarbonate diffuser
- Supplied as standard with warm white [3000K] LED

Installation Notes

Fixed via rear wall mounting plate with cable entry and wired via 3-way termination block



Technical Data

| General | | Electrical | |
|-------------------------------|---------|---------------------------|---------|
| Luminaire Wattage (W) | 9 | Rated Input Current (A) | 0.04 |
| Weight (kg) | 0.70 | Power Factor (pf) | 0.94 |
| Operating Temperature (ta °C) | 0 to 25 | Input Voltage Range (VAC) | 198-264 |
| | | Inrush Current Peak (A) | 13 |
| | | Surge Protection (kV) | 1 |
| | | Conductor Size (mm) | 0.5-1.5 |
| | | Terminal Type | PIANO 3 |
| Light Output | | | |
| Lumens (lm) | 550 | | |
| Efficacy (lm/W) | 61 | | |
| LED | | | |
| CCT (K) | 3000 | | |
| CRI | 84 | | |
| Driver | | | |
| Driver Current (mA) | 350 | | |
| Forward Voltage (V) | 21 | | |

Order Code: XCPL9WW
9W - Porch Light LED - Fixed Output - 3000K

Dimensions

| | |
|-----------|-----|
| A (mm) | 180 |
| B (mm) | 135 |
| Dia. (mm) | 90 |

Line Drawing

