

Order Code: XCRL100DLPC

100W - Outdoor Road Lantern - IP65 - Photocell Sensor - 6000K



Features

- Ideal for replacement of SON fixtures or Metal Halide fixtures
- Available in 2 sizes
- Available in 3 different outputs
- Photocell option available
- Mounted via side-entry 48mm [30W/60W] or 60mm dia. spigot
- High quality toughened safety glass
- Up to 120 lumens per watt efficacy

Construction

- Aluminium body finished in grey [RAL 7037]
- Supplied as standard with daylight [6000K] LED



Technical Data

General		Electrical	
Luminaire Wattage (W)	100	Rated Input Current (A)	0.65
Weight (kg)	5.20	Power Factor (pf)	0.97
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	100-240
Light Output		Inrush Current Peak (A)	52.5
		Surge Protection (kV)	6
		Conductor Size (mm)	1
Lumens (lm)	12000	Terminal Type	Bare wire
Efficacy (lm/W)	120		
LED			
CCT (K)	6000		
CRI	70		
Macadam Elipses	3		
Driver			
Driver Current (mA)	464		
Forward Voltage (V)	42.9		

Order Code: XCRL100DLPC

100W - Outdoor Road Lantern - IP65 - Photocell Sensor - 6000K

Dimensions

A (mm)	715
B (mm)	280
C (mm)	138

Line Drawing

