xcite LED Lighting
Data Sheet

Order Code: XCRL30DL

30W - Outdoor Road Lantern - IP65 - 6000K



Features

- Ideal for replacement of SON fixtures or Metal Halide fixtures
- Available in 2 sizes
- Available in 3 different outputs
- Photocell option available
- Mounted via side-entry 48mm [30W/60W] or 60mm dia. spigot
- High quality toughened safety glass
- Up to 120 lumens per watt efficacy

Construction

- Aluminium body finished in grey [RAL 7037]
- Supplied as standard with daylight [6000K] LED



Technical Data

General

Luminaire Wattage (W)	30
Weight (kg)	2.26
Operating Temperature (ta °C)	-20 to 25

Light Output

Lumens (lm)	3600
Efficacy (lm/W)	120

LED

CCT (K)	6000
CRI	70
Macadam Elipses	3

Driver

Driver Current (mA)	135
Forward Voltage (V)	40.3

Electrical

Rated Input Current (A)	0.2
Power Factor (pf)	0.98
Input Voltage Range (VAC)	120-240
Inrush Current Peak (A)	6.35
Surge Protection (kV)	4
Conductor Size (mm)	1
Terminal Type	Bare wire

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk

xcite LED Lighting

Data Sheet


Order Code: XCRL30DL

30W - Outdoor Road Lantern - IP65 - 6000K

Dimensions

A (mm)	500
B (mm)	212
C (mm)	68

Line Drawing



Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk