

Order Code: XCRLSX1

X1 Road Lantern - CCT [3000K/4000K/5000K] + Wattage Selectable



Features

- Wattage adjustable via selector switch [40W/50W/60W]
- CCT adjustable via selector switch [3000K/4000K/5000K]
- Up to 149 lumens per watt efficacy

Construction

- Clear polycarbonate diffuser
- Aluminium body finished in grey [RAL 9007]
- Adjustable bracket for side entry or post-top mounting [42.6mm to 60mm]

Installation Notes

Wired via screwless connector inside main body
Loop in/out push-fit terminal block for quick installation



Technical Data

General		Electrical	
Luminaire Wattage (W)	40W/50W/60W	Rated Input Current (A)	0.19 to 0.27
Weight (kg)	2.55	Power Factor (pf)	0.95 to 0.97
Operating Temperature (ta °C)	0° to 25°	Input Voltage Range (VAC)	220 to 240
		Inrush Current Peak (A)	60
Light Output		Surge Protection (kV)	1KV
Lumens (lm)	6000 to 8700	Conductor Size (mm)	0.5 to 2.5
Efficacy (lm/W)	149	Terminal Type	4 pole piano key
LED			
CCT (K)	3000K/4000K/5000K		
CRI	80		
Macadam Elipses	2.1 to 4.4		
Driver			
Driver Current (mA)	1090		
Forward Voltage (V)	43 to 50		

Order Code: XCRLSX1

X1 Road Lantern - CCT [3000K/4000K/5000K] + Wattage Selectable

Dimensions

A (mm)	480
B (mm)	160
C (mm)	90

Line Drawing

