

**Order Code:** XCRP6630WW

30W - Recessed Edge-lit Panel - 600mm x 600mm - 3000K



### Features

- Ideal for retrofit of existing T5 or T8 fixtures
- Suitable for offices and schools
- 2 sizes available with 2.5mm light guide
- Compatible with [Panel Frame](#) and [Surface Panel Frame](#)
- 3 hours emergency maintained with compatible conversion box [Emergency Kit](#)
- Up to 100 lumens per watt efficacy

### Construction

- Extruded aluminium frame
- High performance opal TP[b] diffuser
- Plug and play driver
- Emergency option available
- Supplied in warm white [3000K], neutral white [4000K], cool white [5000K] or daylight [6000K]



### Technical Data

| General                       |         | Electrical                |                  |
|-------------------------------|---------|---------------------------|------------------|
| Luminaire Wattage (W)         | 30      | Rated Input Current (A)   | 0.13             |
| Weight (kg)                   | 2.75    | Power Factor (pf)         | 0.9              |
| Operating Temperature (ta °C) | 0 to 25 | Input Voltage Range (VAC) | 220-240          |
| Light Output                  |         | Inrush Current Peak (A)   | 14               |
|                               |         | Surge Protection (kV)     | 2                |
|                               |         | Conductor Size (mm)       | 1.5              |
| Lumens (lm)                   | 3000    | Terminal Type             | 2 pole grip wire |
| Efficacy (lm/W)               | 100     |                           |                  |
| LED                           |         |                           |                  |
| CCT (K)                       | 3000    |                           |                  |
| CRI                           | 80      |                           |                  |
| Macadam Elipses               | 4       |                           |                  |

**Order Code:** XCRP6630WW

30W - Recessed Edge-lit Panel - 600mm x 600mm - 3000K

### Dimensions

|        |     |
|--------|-----|
| A (mm) | 595 |
| B (mm) | 595 |
| C (mm) | 10  |

### Line Drawing

