

Order Code: XCSBT528WW

28W - 1500mm Batten - 3000K

Features

- Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- Batten fit PIR option available
- Up to 120 lumens per watt efficacy

Construction

- Steel body in white finish
- High quality opal diffuser to reduce glare
- Integral high quality driver and LED module
- Loop in/out mains connector
- Conduit and BESA fixing points for end or rear cable entry
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]



Technical Data

General

| | |
|-------------------------------|---------|
| Luminaire Wattage (W) | 28 |
| Weight (kg) | 1.10 |
| Operating Temperature (ta °C) | 0 to 25 |

Light Output

| | |
|-----------------|------|
| Lumens (lm) | 3350 |
| Efficacy (lm/W) | 120 |

LED

| | |
|-----------------|------|
| CCT (K) | 3000 |
| CRI | 80 |
| Macadam Elipses | 4 |

Electrical

| | |
|---------------------------|------------------|
| Rated Input Current (A) | 0.13 |
| Power Factor (pf) | 0.9 |
| Input Voltage Range (VAC) | 220-240 |
| Inrush Current Peak (A) | 10 |
| Surge Protection (kV) | 1 |
| Conductor Size (mm) | 1.5 |
| Terminal Type | 3 pole piano key |

Order Code: XCSBT528WW

28W - 1500mm Batten - 3000K

Dimensions

| | |
|--------|------|
| A (mm) | 1500 |
| B (mm) | 55 |
| C (mm) | 58 |
| Fix | 610 |

Line Drawing

