

Order Code: XCSBT555NWM3

55W - 1500mm Batten - 4000K - 3hrs Maintained Emergency

Features

- Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- Batten fit PIR option available
- Up to 119 lumens per watt efficacy

Construction

- Steel body in white finish
- High quality opal diffuser to reduce glare
- Integral high quality driver and LED module
- Loop in/out mains connector
- Conduit and BESA fixing points for end or rear cable entry
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]



Technical Data

General

| | |
|-------------------------------|---------|
| Luminaire Wattage (W) | 55 |
| Weight (kg) | 1.50 |
| Operating Temperature (ta °C) | 5 to 25 |

Light Output

| | |
|-----------------|------|
| Lumens (lm) | 6550 |
| Efficacy (lm/W) | 119 |

LED

| | |
|-----------------|------|
| CCT (K) | 4000 |
| CRI | 80 |
| Macadam Elipses | 4 |

Emergency

| | |
|---------------------------|-----|
| Emergency Lumen Operating | 190 |
| Emergency Wattage (W) | 1 |

Electrical

| | |
|---------------------------|------------------|
| Rated Input Current (A) | 0.25 |
| Power Factor (pf) | 0.9 |
| Input Voltage Range (VAC) | 220-240 |
| Inrush Current Peak (A) | 13 |
| Surge Protection (kV) | 1 |
| Conductor Size (mm) | 1.5 |
| Terminal Type | 4 pole piano key |

Order Code: XCSBT555NWM3

55W - 1500mm Batten - 4000K - 3hrs Maintained Emergency

Dimensions

| | |
|--------|------|
| A (mm) | 1500 |
| B (mm) | 55 |
| C (mm) | 58 |
| Fix | 610 |

Line Drawing

