

Order Code: XCSC40NW

40W - Scoop Adjustable Downlight - 4000K



Features

- Suitable for retail and display areas
- Fully adjustable up to 350° rotation and 45° tilt
- Supplied with polished aluminium reflector - 35° beam angle
- Up to 100 lumens per watt efficacy

Construction

- Die-cast aluminium body finished in white
- Remote driver
- Supplied as standard with neutral white [4000K] LED



Technical Data

General		Electrical	
Luminaire Wattage (W)	40	Rated Input Current (A)	0.27
Weight (kg)	1.14	Power Factor (pf)	0.9
Operating Temperature (ta °C)	-10 to 40	Input Voltage Range (VAC)	220 - 240
		Inrush Current Peak (A)	24.9
		Surge Protection (kV)	1
		Conductor Size (mm)	1.5
		Terminal Type	2-pole screw down
Light Output			
Lumens (lm)	4000		
Efficacy (lm/W)	100		
LED			
CCT (K)	4000		
CRI	80		
Macadam Ellipses	4		
Driver			
Driver Current (mA)	950		
Forward Voltage (V)	24 - 42		

Order Code: XCSC40NW

40W - Scoop Adjustable Downlight - 4000K

Dimensions

C (mm)	145
Cut Out (mm)	155
Dia. (mm)	163

Line Drawing

