xcite LED Lighting
Data Sheet

Order Code: XCSK65DL

IP65 12V 5m LED Strip Kit - 6000K







Features

- Suitable for under cabinet LED strip lighting in kitchens, bars and restaurants
- 500 lumens per metre
- 3M adhesive backing tape
- 5m reel, cuttable every 50mm
- Supplied with mains plug-in 12V driver

Construction

- 4.8W per metre
- Weatherproof IP65 construction
- CRI: Ra>80



Technical Data

General

Operating Temperature (ta °C)	0 to 25

Light Output

Efficacy (lm/W)	104

LED

CCT (K)	6000
CRI	85
Macadam Elipses	4

Driver

Driver Current (mA)	12V CV
Forward Voltage (V)	12

Electrical

Rated Input Current (A)	0.136
Power Factor (pf)	0.77
Input Voltage Range (VAC)	220-240V
Inrush Current Peak (A)	46
Surge Protection (kV)	1
Conductor Size (mm)	Solder Pad
Terminal Type	AWG22

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk

xcite LED Lighting

Data Sheet


Order Code: XCSK65DL

IP65 12V 5m LED Strip Kit - 6000K

Dimensions

A (mm)	5000
B (mm)	8
C (mm)	3
Cut Points (mm)	50

Line Drawing



Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk