

**Order Code: XCSL433NWMS**

33W - Surface module - Fixed output - Microwave sensor - 4000K



**Features**

- Suitable for schools, corridors and general areas
- Available in 2 lengths and 2 outputs
- Surface mounted

**Construction**

- Steel body in white finish
- Opal polycarbonate diffuser
- Rear BESA fixings or side cable entry
- Supplied as standard with neutral white [4000K] LED



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	33	Rated Input Current (A)	0.15
Weight (kg)	1.70	Power Factor (pf)	0.95
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220 to 240
		Inrush Current Peak (A)	80
		Surge Protection (kV)	2
		Conductor Size (mm)	0.5 to 2.5
		Terminal Type	4-POLE GRIP-WIRE
Light Output			
Lumens (lm)	3900		
Efficacy (lm/W)	118		
LED			
CCT (K)	4000		
CRI	80		
Macadam Elipses	<3		
Driver			
Driver Current (mA)	700		
Forward Voltage (V)	41		

**Order Code: XCSL433NWMS**

33W - Surface module - Fixed output - Microwave sensor - 4000K

Dimensions

A (mm)	1203
B (mm)	154
C (mm)	70

Line Drawing

