
xcite LED Lighting
Data Sheet

Order Code: XCSR20MNWCOB

20M COB LED Strip Reel - 7 W/m - 4000K - Silicon



Features

- Suitable for under cabinet LED strip lighting in kitchens, bars and restaurants
- 7W per metre
- Up to 125 lumens per watt efficacy
- 3M adhesive backing tape
- 1m cable tails, pre soldered to strip at both ends

Construction

- 875 lumens per metre
- 416 LED chips per metre for continuous dot free uniform illumination
- Cuttable reel every 38.4mm

3000K | 4000K | 50,000 HOURS | 3YRS WARRANTY | IP20

Technical Data

General

Operating Temperature (ta °C)	0° to 25°

Light Output

Efficacy (lm/W)	125

LED

CCT (K)	4000
CRI	91
Macadam Elipses	1

Driver

Driver Current (mA)	>1460
Forward Voltage (V)	24

Electrical

Rated Input Current (A)	0.03 to 0.67
Power Factor (pf)	0.91
Input Voltage Range (VAC)	AC 220 to 240V
Terminal Type	Solder Pad

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk


Order Code: XCSR20MNWCOB

20M COB LED Strip Reel - 7 W/m - 4000K - Silicon

Dimensions

A (mm)	20000
B (mm)	8
C (mm)	2
Cut Points (mm)	38.4

Line Drawing



Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk