

**Order Code: XCUCL16CT**

CABINET LIGHT CC Cabinet/Shaver Lights 16W - 3000K-4000K



**Features**

- CCT selectable via 2-way selector switch [3000K/4000K]
- Slimline profile for discreet installation
- Up to 125 lumens per watt efficacy

**Construction**

- Extruded plastic body
- LED SMD modules array



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	16	Rated Input Current (A)	0.08
Weight (kg)	0.27	Power Factor (pf)	0.9
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
Light Output		Inrush Current Peak (A)	5
		Surge Protection (kV)	0.5
		Conductor Size (mm)	0.5 to 2.5
Lumens (lm)	2000	Terminal Type	2 core flex
Efficacy (lm/W)	125		
LED			
CCT (K)	3000K/4000K		
CRI	80		
Macadam Ellipses	5		
Driver			
Driver Current (mA)	205		
Forward Voltage (V)	72		

**Order Code:** XCUCL16CT

CABINET LIGHT CC Cabinet/Shaver Lights 16W - 3000K-4000K

### Dimensions

A (mm)	1157
B (mm)	23
C (mm)	37

### Line Drawing

