xcite LED Lighting
Data Sheet

Order Code: XCUCL3CT

CABINET LIGHT CC Cabinet/Shaver Lights 3W - 3000K-4000K



Features

- Slimline profile for discreet installation
- CCT selectable via 2-way selector switch [3000K/4000K]
- Up to 113 lumens per watt efficacy

Construction

- Extruded plastic body
- LED SMD modules array

3000K 4000K | 50,000 HOURS | 3YRS WARRANTY | IP20 | IK05 | IK06

Technical Data

General

Luminaire Wattage (W)	3
Weight (kg)	0.08
Operating Temperature (ta °C)	0 to 25

Light Output

Lumens (lm)	340
Efficacy (lm/W)	113

LED

CCT (K)	3000K/4000K
CRI	80
Macadam Elipses	5

Driver

Driver Current (mA)	85
Forward Voltage (V)	30

Electrical

Rated Input Current (A)	0.02
Power Factor (pf)	0.6
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	5
Surge Protection (kV)	0.5
Conductor Size (mm)	0.5 to 2.5
Terminal Type	2 core flex

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk

xcite LED Lighting

Data Sheet


Order Code: XCUCL3CT

CABINET LIGHT CC Cabinet/Shaver Lights 3W - 3000K-4000K

Dimensions

A (mm)	222
B (mm)	23
C (mm)	37

Line Drawing



Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk