

**Order Code: XCUCL5CT**

CABINET LIGHT CC Cabinet/Shaver Lights 5W - 3000K-4000K



**Features**

- CCT selectable via 2-way selector switch [3000K/4000K]
- Slimline profile for discreet installation
- Up to 100 lumens per watt efficacy

**Construction**

- Extruded plastic body
- LED SMD modules array



**Technical Data**

| General                       |             | Electrical                |             |
|-------------------------------|-------------|---------------------------|-------------|
| Luminaire Wattage (W)         | 5           | Rated Input Current (A)   | 0.03        |
| Weight (kg)                   | 0.10        | Power Factor (pf)         | 0.75        |
| Operating Temperature (ta °C) | 0 to 25     | Input Voltage Range (VAC) | 220-240     |
| <b>Light Output</b>           |             | Inrush Current Peak (A)   | 5           |
| Lumens (lm)                   | 500         | Surge Protection (kV)     | 0.5         |
| Efficacy (lm/W)               | 100         | Conductor Size (mm)       | 0.5 to 2.5  |
| <b>LED</b>                    |             | Terminal Type             | 2 core flex |
| CCT (K)                       | 3000K/4000K |                           |             |
| CRI                           | 80          |                           |             |
| Macadam Ellipses              | 5           |                           |             |
| <b>Driver</b>                 |             |                           |             |
| Driver Current (mA)           | 140         |                           |             |
| Forward Voltage (V)           | 30          |                           |             |

**Order Code:** XCUCL5CT

CABINET LIGHT CC Cabinet/Shaver Lights 5W - 3000K-4000K

Dimensions

|        |     |
|--------|-----|
| A (mm) | 296 |
| B (mm) | 23  |
| C (mm) | 37  |

Line Drawing

