

### Order Code: XCWL23CTHFS

23W - Wallpack CC - IP65 - CCTK Selector [3000K/4000K/6000K] - Microwave sensor



#### Features

- Ideal for retrofit of HID discharge wallpacks
- Suitable for exterior walls and entrance areas
- CCT adjustable via 2-way dip switch [3000K/4000K/6000K]
- Sensor options available
- Up to 70 lumens per watt efficacy

#### Construction

- Polycarbonate body and diffuser
- Integral emergency option available
- CRI: Ra>80



#### Technical Data

##### General

|                               |         |
|-------------------------------|---------|
| Luminaire Wattage (W)         | 23      |
| Weight (kg)                   | 1.40    |
| Operating Temperature (ta °C) | 0 to 25 |

##### Light Output

|                 |              |
|-----------------|--------------|
| Lumens (lm)     | 1600 to 1900 |
| Efficacy (lm/W) | 70           |

##### LED

|                 |                   |
|-----------------|-------------------|
| CCT (K)         | 3000K/4000K/6000K |
| CRI             | >80               |
| Macadam Elipses | 4                 |

##### Driver

|                     |           |
|---------------------|-----------|
| Driver Current (mA) | 700       |
| Forward Voltage (V) | 25.2-30.6 |

##### Electrical

|                           |                  |
|---------------------------|------------------|
| Rated Input Current (A)   | 0.12             |
| Power Factor (pf)         | 0.9              |
| Input Voltage Range (VAC) | 220-240          |
| Inrush Current Peak (A)   | 10               |
| Surge Protection (kV)     | 1                |
| Conductor Size (mm)       | 2.5              |
| Terminal Type             | 3 pole piano key |

**Order Code:** XCWL23CTHFS

23W - Wallpack CC - IP65 - CCTK Selector [3000K/4000K/6000K] - Microwave sensor

### Dimensions

|        |     |
|--------|-----|
| A (mm) | 307 |
| B (mm) | 257 |
| C (mm) | 105 |

### Line Drawing

