

Order Code: XCWL23CTM3HFSPC

23W - Wallpack CC - IP65 - CCTK Selector [3000K/4000K/6000K] - 3hrs Maintained Emergency - Microwave sensor & Photocell



Features

- Ideal for retrofit of HID discharge wallpacks
- Suitable for exterior walls and entrance areas
- CCT selectable via 2-way dip switch [3000K/4000K/6000K]
- Sensor options available
- Up to 70 lumens per watt efficacy

Construction

- Polycarbonate body and diffuser
- Integral emergency option available
- CRI: Ra>80



Technical Data

| General | | Electrical | |
|-------------------------------|-------------------|---------------------------|------------------|
| Luminaire Wattage (W) | 23 | Rated Input Current (A) | 0.12 |
| Weight (kg) | 2.00 | Power Factor (pf) | 0.9 |
| Operating Temperature (ta °C) | 5 to 25 | Input Voltage Range (VAC) | 220-240 |
| | | Inrush Current Peak (A) | 10 |
| | | Surge Protection (kV) | 1 |
| | | Conductor Size (mm) | 2.5 |
| | | Terminal Type | 4 pole piano key |
| Light Output | | | |
| Lumens (lm) | 1600 to 1900 | | |
| Efficacy (lm/W) | 70 | | |
| LED | | | |
| CCT (K) | 3000K/4000K/6000K | | |
| CRI | >80 | | |
| Macadam Elipses | 4 | | |
| Driver | | | |
| Driver Current (mA) | 700 | | |
| Forward Voltage (V) | 25.2-30.6 | | |
| Emergency | | | |
| Emergency Lumen Operating | 150 | | |
| Emergency Wattage (W) | 2 | | |

Order Code: XCWL23CTM3HFSPC

23W - Wallpack CC - IP65 - CCTK Selector [3000K/4000K/6000K] - 3hrs Maintained Emergency - Microwave sensor & Photocell

Dimensions

| | |
|--------|-----|
| A (mm) | 307 |
| B (mm) | 257 |
| C (mm) | 105 |

Line Drawing

